

**CHCNAV**

**i90**

**IMU-RTK GNSS  
RECEIVER**



**SURVEYING &  
ENGINEERING**

# HIGH-PERFORMANCE IMU RTK GNSS RECEIVER

The i90 GNSS receiver integrates professional IMU-RTK technology to provide a robust and accurate positioning, in any circumstances. It combines state-of-the-art GNSS RTK engine, a calibration-free high-end IMU sensor and advanced GNSS tracking capabilities to dramatically increase RTK availability and reliability.

The i90 automatic pole-tilt compensation boosts survey and stakeout speed by up to 30%. Construction and land surveying projects are achieved with high productivity and reliability pushing the boundaries of conventional GNSS RTK survey.

## FULL GNSS POSITIONING

**Combining GPS, Glonass, Galileo and BeiDou constellations.**

The embedded 624-channel GNSS technology takes benefit from all GPS, GLONASS, Galileo and BeiDou signals and provides robust RTK position availability and reliability.

## HASSLE-FREE IMU-RTK SURVEYING

**Dramatically increase RTK availability.**

No complicated calibration process, rotation, leveling or accessories are necessary with the i90. Simply rock the range pole a few times to initialize the i90 internal IMU module and enable GNSS RTK survey in difficult field environment.

## EXTENDED CONNECTIVITY

**Instant NFC pairing of your controller.**

The i90 GNSS combines high-end connectivity modules: Bluetooth, Wi-Fi, NFC, 4G, and UHF radio modem. The 4G modem brings ease of use when working within RTK networks. The internal UHF radio modem allows long-distance base-to-rover surveying up to 5 km.

## EXTENDED CONNECTIVITY

**Boost survey and stakeout speed by up to 30%.**

The i90 GNSS build-in IMU ensures interference-free and automatic pole-tilt compensation in real-time. 3 cm accuracy is achieved with pole-tilt range of up to 30 degrees.



**ENABLE GNSS RTK  
ANYTIME, ANYWHERE**

---



# SPECIFICATIONS

GNSS Performance <sup>(1)</sup>	
Channels	624 channels
GPS	L1 C/A, L2C, L2P, L5
GLONASS	L1, L2, L3
Galileo	E1, E5a, E5b, E6
BeiDou	B1, B2, B3
SBAS	L1, L5
QZSS	L1, L2, L5, L6

GNSS Accuracies <sup>(2)</sup>	
Real time kinematics (RTK)	Horizontal: 8 mm+ 0.5 ppm RMS Vertical: 15 mm+ 0.5 ppm RMS Initialization time: < 10 s Initialization reliability: > 99.9%
Post-processing kinematics (PPK)	Horizontal: 2.5 mm+ 1 ppm RMS Vertical: 5 mm+ 1 ppm RMS
Post-processing static	Horizontal: 2.5 mm+ 0.1 ppm RMS Vertical: 3.5 mm+ 0.4 ppm RMS
Code differential	Horizontal: 0.25 m RMS
Autonomous	Horizontal: 1.5 m RMS Vertical: 3 m RMS
Positioning rate	Up to 10 Hz
Time to first fix <sup>(3)</sup>	Cold start: < 45 s Hot start: < 10 s Signal re-acquisition: < 1 s
RTK tilt -compensated	Additional horizontal pole-tilt uncertainty typically less than 10 mm+ 0.7 mm/° tilt


Hardware	
Size (LxWxH)	159 mmx 150 mmx 110 mm (6.3 in x 5.9 in x 4.3 in)
Weight	1.26 kg (2.77 lb)
Environment	Operating: -40°C to +65°C (-40°F to +149°F) Storage: -40°C to +85°C (-40°F to +185°F)
Humidity	100% condensation
Ingress protection	IP67 waterproof and dustproof, protected from temporary immersion to depth of 1 m
Shock	Survive a 2-meter pole drop
Tilt sensor	Calibration-free IMU for pole-tilt compensation. Immune to magnetic disturbances. EBubble leveling
Front panel	4 LED indicators 1.46" OLED Display

Certifications	
FCC Part 15 (class B Device), FCC Part 22, 24, 90; CE Mark; NGS Antenna Calibration; MIL-STD 883C, Method 2000.7	

Communication	
Network modem	Integrated 4G modem LTE (FDD): B1, B2, B3, B4, B5, B7, B8, B20 DC-HSPA+/HSPA+/HSPA/UMTS: B1, B2, B5, B8 EDGE/GPRS/GSM 850/900/1800/1900 MHz
Wi-Fi	802.11 b/g/n, access point mode
Bluetooth ®	v4.1
Ports	1 x 7-pin LEMO port (external power, RS-232) 1 x USB Type-C port (data download, firmware update) 1 x UHF Antenna port (TNC female)
UHF radio	Standard Internal Rx/Tx: 410 - 470 MHz Transmit Power: 0.5 W to 2 W Protocol: CHC, Transparent, TT450, 3AS Link rate: 9600 bps to 19200 bps Range: Typical 3 km to 5 km RTCM2.x, RTCM3.x, CMR input / output HCN, HRC, RINEX 2.11, 3.02 NMEA0183 output NTRIP Client, NTRIP Caster
Data formats	
Data storage	32 GB internal memory
Electrical	
Power consumption	5 W (depending on user settings)
Li-ion battery capacity	2 x 3400 mAh, 7.4 V
Operating time on internal battery <sup>(4)</sup>	UHF receive/transmit (0.5 W): 6 h to 12 h Cellular receive only: up to 12 h Static: up to 12 h
External power input	9 V DC to 28 V DC



\*All specifications are subject to change without notice.  
(1) Compliant, but subject to availability of BDS ICD and Galileo commercial service definition. BDS B3 and Galileo E6 will be provided through future firmware upgrade. (2) Accuracy and reliability are determined under open sky, free of multipaths, optimal GNSS geometry and atmospheric condition. Performances assume minimum of 5 satellites, follow up of recommended general GPS practices. (3) Typical observed values. (4) Battery life is subject to operating temperature.



© 2020 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision May 2020.

WWW.CHCNAV.COM | SALES@CHCNAV.COM

CHC Navigation Headquarter  
Shanghai Huace Navigation Technology Ltd.  
599 Gaojing Road, Building D,  
Shanghai, 201702, China ,  
+86 21 54260273

CHC Navigation Europe  
Infopark Building , Sétány 1, 1117  
Budapest, Hungary  
+36 20 235 8248 +36 20 5999 369  
info@chcnav.eu

CHC Navigation USA LLC  
16412 N 92nd Street, Suite 115,  
85 260 Scottsdale, Arizona, USA,  
+1 480 676 4306

CHC Navigation India  
409 Trade Center, Khokhra Circle,  
Maninagar East, Ahmedabad,  
Gujarat, India  
+91 90 99 98 08 02